

800 nits Sunlight Readable | Wi-Fi 6 Technology | Sensitive Digitizer Support

Windows 11

Deliver the thinnest and lightest rugged tablet, TB170, to ramp up your work production. Weighing at just 990g and featuring with slim 15mm edge, the 10.1-inch rugged tablet is engineered to give your optimum portability to finish tasks with a comfortable digitizer at ease. Operated in Windows 11 and a faster Wi-Fi 6 connection, TB170 safeguards the scanned data stability and accuracy under the refreshed system look for every user working in manufacturing, field service, and warehousing.

Advanced Technology: Wi-Fi 6

Its dependable Bluetooth® 5.2 and low-latency Wi-Fi 6 connectivity is perfectly suited for industries requiring wider space movement, such as large warehouses and distribution centers. The faster 9.6 Gbps speed rate stabilizes the wireless connection for Internet phone calls and meetings even when a bunch of devices is connected.

Thin and Light Tablet yet Durable

The light tablet with a slim 15mm edge is designed for workers to comfortably capture data and check inventory in high portability from day to night. For an easy touch and view, the 10.1" display supports glove and wet touch mode and is sunlight readable with 800 nits. To meet enterprise rigorous scenarios, TB170 withstands dust and water drops with IP65 protection and is tested for 6 ft / 1.5 m onto concrete. The MIL-STD-810G standard assures an overall environmental vibration and humidity.

Smooth Input, Greater Output

Coming with a sensitive digitizer, the TB170 empowers associates to write a memo or a signature on the 10-point multi-touch panel. Paired with a superior 2D engine, it collects data efficiently by pressing its programmable key. These integrated I/O ports (USB TypeA&C, SIM Card Reader, RJ45 Ethernet Port, Replaceable DC jack, Micro HDMI, SDXC Card Reader, 3.5mm Audio jack) allow external equipment to synchronize data once they are connected.

Full-shift Battery Life

The high capacity 4800mAh battery ensures workers to cope with long work shifts of up to 10 hours. With the hot-swappable design, it's no need to shut down your TB170 or interrupt work activity to sustain a consecutive task. As mobility is highly valued in field service, the TB170 can be carried around on a shoulder strap or hand strap; for the static workplace, office and vehicle docking are your best solutions to meet all scanning requirements.

Features

- Windows 11 enterprise operating system
- * 10.1" (1920 x 1200) IPS 800 nits sunlight readable
- Hot-swappable battery design with a capacity 4800mAh up to 10 hours
- Lightest and thinnest casing only 990 g with 15 mm
- 5 physical buttons: power, vol+, vol-, 2 programmable keys
- Rugged Design: IP65, MIL-STD-810G, 1.5m drop resistance
 Latest wireless technology: Wi-Fi 6 802.11ax. & Bluetooth® 5.2
- Simply write and highlight on EETI digitizer pen
- Common and useful I/O ports you name including USB TypeA&C, Ethernet
- Various Accessories: Shoulder-Strap / Hand-Strap/ Vehicle docking/ Office docking / Brief Case Handle
- Support Trusted Platform Module (TPM) 2.0





TB170

Specifications



System Features

OS Windows 11 Enterprise

2.6Ghz, Intel® Gemini Lake-R Celeron N4120 CPU LPDDR4 8GB on Board / 128GB eMMC Memory Others TPM (Trusted Platform Module) 2.0 support

Display

10.1"" (1920 x 1200) IPS 800 nits Sunlight Readable

10-point multi-touch, support glove mode and wet-touch mode

Buttons / Keypad

5 Physical Buttons power, vol+, vol-, 2 programmable keys

Indicator Type

LEDs, Vibrator

I/O Interfaces

USB USB 3.1 Type A x 1

USB 3.1 Type C x 1 SIM Slot SIM Card Reader [Nano]

Expansion Slot Docking connector RJ45 Gigabit Ethernet Port

Replaceable DC jack Micro HDMI

SDXC Card Reader [Micro]

Reset hole

POGO PIN POGO pin

Audio

Microphone, speaker and 3.5mm audio jack

Power Source

Main Battery Battery:7.6V, 4800mAh / 36.5 Wh

Backup Battery: 7.4V, 142mAh / 1.05Wh

Hot-swappable

Battery Operation: up to 10 hours

Communication

Camera 2MP front camera [Win 10 Hello Optional]

8MP rear camera, Auto Focus, Flash

Bluetooth® 5.2 supported Bluetooth[®] Wi-Fi 6 [802.11ax] (2X2 MIMO) WI AN

WWAN Optional Sierra EM7565 [North America/EMEA]

Optional Quectel EM06-E{EMEA} GPS/ GLONASSS/ GALILEO

GPS 9 Axis MEMS sensor [Accelerometer, eComass, Gyroscope] Sensor

Ambient Light Sensir

Proximity Sensor

Symbologies

Optional 1D/2D Barcode Reader

Enclosure

283 x 192 x15 (mm) Dimensions

Weight 990g

Environmental

Operating temperature -10~50°C Storage temperature -20~60°C

Durability

Drop Specification 1.5m Sealing **IP65**

Vibration/ Tumble test MIL-STD 810G

Regulatory Approvals

CE, FCC, BSMI, NCC

Accessories

Shoulder-Strap X-strap

Vehicle Docking Office Docking Brief Case Handle EETI Digitizer Pen, B-type







Headquarters

Taipei, Taiwan http://www.ute.com e-mail: info@hq.ute.com

unitech America

Los Angeles

http://us.ute.com e-mail: info@us.ute.com

http://can.ute.com info@can.ute.com

http://latin.ute.com e-mail: info@latin.ute.com

unitech Asia Pacific & Middle East

http://apac.ute.com info@apac.ute.com / info@india.ute.com

http://mideast.ute.com info@mideast.ute.com

unitech Europe

Tilburg / Netherlands

http://eu.ute.com e-mail: info@eu.ute.com

unitech Japan

http://jp.ute.com e-mail: info@jp.ute.com

unitech Greater China

Beijing, Shanghai, Guang Zhou, Xiamen http://cn.ute.com info@cn.ute.com Taipei http://tw.ute.com info@tw.ute.com

